



RelayCaster server appliances offer a turn-key solution that enable optimized transmission of IPTV streams. By using the RelayCaster Streaming Protocol (RSP), reliability and data rates of streaming live content in wireless networks or along lossy long distance links can be greatly improved. RelayCaster servers allow for building cost-effective Content Delivery Networks (CDN) using the public Internet infrastructure. At the same time, RelayCaster servers can be used as powerful tool for performing various conversions between multicast and unicast networking. Being compatible with existing

gateways, transcoders, streaming servers, conditional access systems, and set-top boxes, RelayCaster appliances can be seamlessly integrated into your existing infrastructure.

Using RSP as streaming protocol between two RelayCaster servers allows for the optimized transmission of IPTV streams to remote company sites, data centers, or networks. Compared to streaming with UDP or RTP, RSP greatly reduces packet loss. Compared to content distribution with TCP or higher-level protocols such as FTP or HTTP, RSP offers much higher bandwidths for transmission of live content over lossy long distance links.

RelayCaster 1000

RelayCaster Streaming Protocol (RSP)




Application areas

- Optimized IPTV streaming for lossy long-distance links in Content Delivery Networks (CDN)


- Optimized IPTV streaming to clients in lossy wireless networks

- Multicast-unicast-multicast bridging for IPTV

- Multicast-unicast conversion for wireless IPTV networks




RSP can also be employed as client-side protocol on wireless clients or set-top boxes.



A pair of RelayCaster servers can be used to transparently convert between multicast and unicast. This allows for 'bridging' network segments that do not support multicast.



Today's commodity devices and infrastructures for wireless networks often do not support IPTV multicast. RelayCaster appliances overcome these limitations by transparently recasting IPTV multicast streams available in the wired network to unicast streams for wireless clients.



<ul style="list-style-type: none"> ■ IP Streaming 	<ul style="list-style-type: none"> ■ 2x 1000 BaseT Gigabit Ethernet <ul style="list-style-type: none"> ■ 1x Mgmt (Management and Streaming) ■ 1x GbE (Streaming only) ■ MPEG Transport Stream (MPEG-TS) for SDTV and HDTV <ul style="list-style-type: none"> ■ MPEG-2 ■ MPEG-4 (AVC/H.264) ■ MPEG Audio, AC3, ... ■ Protocols <ul style="list-style-type: none"> ■ Unicast / Multicast / Broadcast ■ UDP ■ RTP over UDP ■ RelayCaster Streaming Protocol (RSP) (optional) ■ Output rate for receiving UDP and sending UDP <ul style="list-style-type: none"> ■ 1x incoming stream: sending up to 850 Mbps, or 150 SDTV streams, or 90 HDTV streams ■ Several incoming streams: receiving up to 600 Mbps, and sending up to 600 Mbps, or 100 SDTV streams, or 62 HDTV streams ■ Output rate for receiving UDP and sending RSP <ul style="list-style-type: none"> ■ Several incoming streams: receiving up to 400 Mbps and sending up to 400 Mbps, or 70 SDTV streams, or 45 HDTV streams (simulated 1% PLR, 50 ms delay) ■ Output rate for receiving RSP and sending UDP <ul style="list-style-type: none"> ■ Several incoming streams: receiving up to 400 Mbps and sending up to 400 Mbps, or 70 SDTV streams, or 45 HDTV streams (simulated 1% PLR, 50 ms delay)
<ul style="list-style-type: none"> ■ Free Software Developer Kit (SDK) 	<ul style="list-style-type: none"> ■ Fully programmable and remotely controllable using C++ API (Windows, Linux, Mac OS), PHP or XML-RPC (all platforms) ■ Based on award winning Network-Integrated Multimedia Middleware (NMM) by Motama
<ul style="list-style-type: none"> ■ Administration 	<ul style="list-style-type: none"> ■ Linux system (kernel 2.6.x) ■ Web interface (http/https) ■ ssh ■ Integrated LCD panel: System setup and monitoring
<ul style="list-style-type: none"> ■ Hardware 	<ul style="list-style-type: none"> ■ 1 U, 19" rack mountable ■ 1x HDD 3,5" (24/7) ■ 2 GB main memory ■ VGA ■ 2x USB ■ Height x Width x Depth <ul style="list-style-type: none"> ■ 43 mm (1.7") x 426 mm (16.8") x 356 mm (14.0") ■ Voltage: 100V – 240V AC, 50-60 Hz ■ Weight: 6 kg ■ Power consumption: <ul style="list-style-type: none"> ■ < 6 W (standby), 50 W (idle) to 150 W (loaded) ■ High-quality server appliance assembled in Germany

RelayCaster 1000

RelayCaster Streaming Protocol (RSP)



Motama GmbH
 Lortzingstr. 10
 66111 Saarbrücken
 Germany
www.motama.com

© 2010 Motama. All rights reserved.
 The information contained herein are subject to change without prior notice and do not carry any contractual obligation for Motama.