



TVCaster 600-C CI

Application areas

- Live TV broadcast with unicast/multicast
- Personal TV access
- Customized IPTV workflows

TVCaster by Motama represents the next generation of IPTV server appliances. TVCaster is a turn-key solution offering all cutting-edge functionality you expect from an integrated DVB receiver, descrambler, remultiplexer, and IP streaming server. In addition, TVCaster offers advanced features, such as ultra-fast channel switching for individual users, integrated video recorder, extended streaming protocols, and clustering support. This all comes with unmatched openness and full programmability that allows you to seamlessly integrate the TVCaster appliance into your IPTV workflow.



-
- | | |
|---|--|
| <ul style="list-style-type: none"> ■ DVB to IP gateway | <ul style="list-style-type: none"> ■ 6x DVB-C input in 3 U unit ■ 6x Common Interface (CI) slot for CAM supporting multi-service descrambling (EN50221) ■ Remultiplexer: Multi Program Transport Stream (MPTS) to Single Program Transport Stream (SPTS) ■ PID filtering ■ SDT/EIT filtering ■ PAT pass-through / generation |
|---|--|
-
- | | |
|--|---|
| <ul style="list-style-type: none"> ■ Support for multiple modes / user groups | <ul style="list-style-type: none"> ■ Corporate Mode: Creation of unicast / multicast streams ■ Home Mode: Distinct assignment of tuners to clients with full section of all available TV channels and ultra-fast channel switching ■ Middleware Mode: Freely programmable stream processing on appliance or network wide |
|--|---|
-
- | | |
|---|--|
| <ul style="list-style-type: none"> ■ Free Software Developer Kit (SDK) | <ul style="list-style-type: none"> ■ Fully remotely controllable using C++ API (Windows, Linux, Mac OS X), PHP, or XML-RPC (all platforms) ■ Client-side sample application, including channel switching ■ Full integration into distributed stream processing ■ Based on award winning Network-Integrated Multimedia Middleware (NMM) by Motama |
|---|--|
-

TVCaster 600-C CI

-
- IP Streaming
 - 2x 1000 BaseT Gigabit Ethernet
 - 1x Mgmt (Management and Streaming)
 - 1x GbE (Streaming only)
 - Output rate:
 - up to 700 Mbps
 - or 70 SDTV streams
 - or 43 HDTV streams
 - MPEG Transport Stream (MPEG-TS) for SDTV and HDTV
 - MPEG-2
 - MPEG-4 (H.264)
 - MPEG Audio, AC3, ...
 - Protocols:
 - Unicast / Multicast / Broadcast
 - UDP
 - RTP over UDP
 - Optimized TCP streaming (reliable)
-
- Comfort features
 - Automatic channel search
 - Server-side electronic program guide (EPG)
 - Fully programmable digital video recorder with integrated hard disk
-
- Administration
 - Linux system (kernel 2.6.x)
 - Web interface (http/https)
 - ssh
 - ftp
 - Integrated LCD panel: System setup and monitoring
-
- Hardware
 - 3 U, 19" rack mountable
 - 6x DVB-C input: IEC F-type (female)
 - 6x CI slots for Conditional Access Modules (CAM)
 - 1x HDD 3,5" with 1 TB (24/7)
 - 2 GB main memory
 - VGA
 - 4x USB
 - 1x DVD-ROM drive
 - Height x Width x Depth
 - 130 mm (5.1") x 430 mm (16.9") x 460 mm (18.1")
 - Voltage: 100V - 240V AC, 50-60 Hz
 - Weight: 17.0 kg
 - Power consumption:
 - < 6 W (standby), 115 W (idle) to 130 W (loaded)
 - High-quality server appliance assembled in Germany
-

Application areas

- Live TV broadcast with unicast/multicast
- Personal TV access
- Customized IPTV workflows



Motama GmbH
 Lortzingstr. 10
 66111 Saarbrücken
 Germany
www.motama.com

© 2010 Motama. All rights reserved.
 The information contained herein are subject to change without prior notice and do not carry any contractual obligation for Motama.

DVB and the DVB logos are Trademarks of the DVB project.